



Turbine Upgrade Guide

CONTENTS

1. Pre-Upgrade Health Check	2
2. Post-Upgrade/Maintenance Checklist	1
3. Turbine 26.3.3 Upgrade Instructions	1
4. Turbine 26.2.3 Upgrade Instructions	1
5. Turbine 26.1.4 Upgrade Instructions	1
6. Turbine 26.1.3 Upgrade Instructions	1
7. Turbine 26.1.2 Upgrade Instructions	1
8. Turbine 26.1.1 Upgrade Instructions	1
9. Turbine 26.1.0 Upgrade Instructions	1
10. Turbine 26.0.3 Upgrade Instructions	1
11. Turbine 25.5.1 Upgrade Instructions	3
12. Turbine 25.5.0 Upgrade Instructions	1
13. Turbine 25.4.3 Upgrade Instructions	1
14. Turbine 25.4.2 Upgrade Instructions	1
15. Turbine 25.4.1 Upgrade Instructions	1
16. Turbine 25.3.4 Upgrade Instructions	1
17. Turbine 25.3.2 Upgrade Instructions	1
18. Turbine 25.3.1 Upgrade Instructions	1

1. Pre-Upgrade Health Check

Node Status

- Check that all Nodes are in Ready state

```
kubectl get nodes -owide
```

- If any nodes are in NotReady, SchedulingDisabled, etc then it would be recommended to review and fix them before upgrading.

Pod Status

- Check that all pods are in Running state and the pod values are matching 1/1, 3/3, etc.

```
kubectl get pods -A
```

- If any pods are not running i.e, 0/1, 2/3, CrashLoopBackoff, Error, etc then it would be advised to review the issue and fix it prior to upgrading

Cluster Status

- Check that Kubernetes is up and running and healthy.

```
kubectl cluster-info
```

- If Kubernetes indicates that it is not healthy then review and establish where the issue is prior to upgrading.

etcd health

- etcd needs to be in a stable state prior to upgrading any issues

```
for pod in $(kubectl get pods -l component=etcd -n kube-system \
-o jsonpath='{.items[*].metadata.name}')
do
    echo "### etcd pod : ${pod} ###"
    kubectl -n kube-system exec ${pod} -- /bin/sh \
        -c "ETCDCTL_API=3 etcdctl \
        --cert=/etc/kubernetes/pki/etcd/server.crt \
        --key=/etc/kubernetes/pki/etcd/server.key \
        --cacert=/etc/kubernetes/pki/etcd/ca.crt \
        endpoint health"
done
```

- Should any other states be listed on the output then it would be advised to investigate the logs of the pod to establish the issue

Hangfire Status

- Check that Hangfire is running and there is no large amount of Enqueued Jobs
- It would be recommended to grab a screenshot of the Hangfire Dashboard prior to upgrading to check the amount processed for Deleted Jobs

Logging Status

11. Turbine 25.5.1 Upgrade Instructions

Use these upgrade instructions to upgrade your instance of Turbine 25.5.1 The instructions are organized by subsections of this document that will help you upgrade by specific installation type, whether you have an embedded or existing cluster installation.

Upgrade Turbine on Embedded Cluster Installations

Use the following instructions to upgrade this version of Swimlane on an embedded cluster installation.

Prerequisites:

- Turbine version 25.4.1
- MongoDB 7.0.24

Important! Swimlane recommends that you perform a MongoDB backup prior to starting this update. For more information, see [Backup and Restore on an Embedded Cluster with Snapshots](#).

Upgrade Instructions

1. SSH into any node in your deployment.
2. Scale down EKCO and kotsadm-qlite.
Note: EKCO and Kotsadm-qlite will automatically scale back up after the script in Step 3 has completed.

```
kubectl -n kurl scale deployment ekc-operator --replicas=0
```

```
kubectl -n default scale statefulsets kotsadm-qlite --replicas=0
```
3. Execute the following command to begin the Turbine Platform Installer component upgrade:

```
curl -sSL https://kurl.sh/turbine-turbine-25-5-1 | sudo bash -s ha
```


Note: If you have configured SELinux, firewall, or proxy add this to the end of the command above: `installer-spec-file=se.yaml`. The se.yaml is the installer patch file created by you as described in: <https://docs.swimlane.com/turbine-installer/overriding-installer-settings>.
4. After the install script has completed, log in to the Turbine Platform Installer dashboard (<https://<SwimlaneDNS>:8800>).
5. Go to the Version History tab and click **Check For Updates**.
6. A pop-up window appears, click **Go to the updated version** and click Configure.
7. Click **Deploy** on the new 25.5.1 version with the highest sequence number at the top of the versions list.
8. Once the Application tab shows 'Ready' your upgrade is complete.

Upgrade Turbine on Existing Cluster Installations

Prerequisites:

- Turbine version 25.4.1
- MongoDB 7.0.24

21. Turbine 25.1.6 Upgrade Instructions

Turbine Upgrade Instructions

Use these upgrade instructions to upgrade your instance of Turbine 25.1.6. The instructions are organized by subsections of this document that will help you upgrade by specific installation type, whether you have an embedded or existing cluster installation.

Upgrade Turbine on Embedded Cluster Installations

Use the following instructions to upgrade this version of Swimlane on an embedded cluster installation.

Prerequisites:

- Turbine version 25.0.8
- MongoDB 7.0.19

Note: If you are already on version 25.1.2, no infrastructure upgrade is required. Proceed to step 4

Important! Swimlane recommends that you perform a MongoDB backup prior to starting this update. For more information, see [Backup and Restore on an Embedded Cluster with Snapshots](#).

Upgrade Instructions

1. SSH into any node in your deployment.
2. Scale down EKCO and kotsadm-qlite.

Note: EKCO and Kotsadm-qlite will automatically scale back up after the script in Step 3 has completed.

```
kubectl -n kurl scale deployment ekc-operator --replicas=0
```

```
kubectl -n default scale statefulsets kotsadm-qlite --replicas=0
```

3. Execute the following command to begin the Turbine Platform Installer component upgrade:

```
curl -sSL https://kurl.sh/turbine-turbine-25-1-6 | sudo bash -s ha
```

Note: If you have configured SELinux, firewall, or proxy add this to the end of the command above:

```
installer-spec-file=se.yaml
```

The se.yaml is the installer patch file created by you as described in:

https://docs.swimlane.com/turbine_installer/embedded-cluster-install/overriding-installer-settings/overriding-installer-settings.htm

4. After the install script has completed, log in to the Turbine Platform Installer dashboard (<https://<SwimlaneDNS>:8800>).
5. Go to the Version History tab and click **Check For Updates**.
6. A pop-up window appears. click **Go to the updated version** and click **Configure**.

31. Turbine 24.3.6 Upgrade Instructions

Turbine Upgrade Instructions

Use these upgrade instructions to upgrade your instance of Turbine 25.x. The instructions are organized by subsections of this document that will help you upgrade by specific installation type, whether you have an embedded or existing cluster installation.

Upgrade Turbine on Embedded Cluster Installations

Use the following instructions to upgrade this version of Swimlane on an embedded cluster installation.

Prerequisites:

- Turbine version 24.3.2
- MongoDB 6.0.18

Important! Swimlane recommends that you perform a MongoDB backup prior to starting this update. For more information, see [Backup and Restore on an Embedded Cluster with Snapshots](#).

Upgrade Instructions

1. SSH into any node in your deployment.
2. Scale down EKCO and kotsadm-rqlite.

Note: EKCO and Kotsadm-rqlite will automatically scale back up after the script in Step 3 has completed.

```
kubectl -n kurl scale deployment ekc-operator --replicas=0  
  
kubectl -n default scale statefulsets kotsadm-rqlite --replicas=0
```

3. Execute the following command to begin the Turbine Platform Installer component upgrade:

```
curl -sSL https://kurl.sh/turbine-turbine-24-3-6 | sudo bash -s ha
```

NOTE: If you have configured SELinux, add this to the end of the command above:

```
installer-spec-file=se.yaml
```

4. After the install script has completed, log in to the Turbine Platform Installer dashboard (<https://<SwimlaneDNS>:8800>).
5. Go to the Version History tab and click **Check For Updates**.
6. A pop-up window appears, click **Go to the updated version** and click Configure.
7. Click **Deploy** on the new 24.3.6 version with the highest sequence number at the top of the versions list.
8. Once the Application tab shows 'Ready' your upgrade is complete.

Upgrade Turbine on Existing Cluster Installations

41. Turbine 23.5.6 Upgrade Instructions

Use these upgrade instructions to upgrade your instance of Turbine 23.x. The instructions are organized by subsections of this document that will help you upgrade by specific installation type, whether you have an embedded or existing cluster installation.

Known Issue with Embedded/Existing Cluster/helm Installations:

We are aware of an issue where the user is 'unable to generate a URL while creating a webhook'. There is a workaround for that for now. This script which can be used on all deployment methods, for KOTS (existing or embedded clusters) and for helm deployments. Contact Support for additional details.

Instructions:

- 1. Set the value for the NS variable in line 5 to the Kubernetes namespace where Turbine has been installed.**
 - KOTS existing cluster and Helm deployments allow setting the namespace where the app is installed.
 - KOTS embedded cluster should be set to "default".
- 2. Copy the script to a computer where you have access to the Kubernetes cluster.**

```
#!/bin/bash
set -e
# Set the Kubernetes namespace where Turbine is installed, this should be
"default" for a Turbine installation with an embedded cluster
# NS=default
NS=
[[ -z $NS ]] && echo "This script requires that you set the name of the
Kubernetes namespace where Turbine is installed in the NS variable." && exit
1

configmap=$(kubectl -n $NS get configmap tenant-services -o
jsonpath='{.data.turbine\-\init\-\tenant\-\job\.yaml}')
tenants=$(kubectl get ns -l "app.kubernetes.io/name=\"tenant-services\" -o
json | jq -r '.items[] | .metadata.labels.\"tenant.swimlane.io/account-id\" +
\";\" + .metadata.labels.\"tenant.swimlane.io/tenant-id\"')
IFS=$'\n'
for i in $tenants;do
    accountid=$(echo $i | cut -d";" -f1)
    tenantid=$(echo $i | cut -d";" -f2)
    yaml=$(echo "$configmap" | sed -r -e "s/REPLACE_ACCOUNT_ID/${accountid}/g"
-e "s/REPLACE_TENANT_ID/${tenantid}/g")
    echo "$yaml" | kubectl -n tenant$tenantid apply -f -
done
```

3. Run the script on the host with a command like "chmod +x script.sh && ./script.sh"
4. The script will show the output of the kubectl command which applies the job manifest for each tenant

```
$ chmod +x script.sh && ./script.sh
job.batch/tenant-init-791dac50-10cc-4096-944f-a2ae98560d1a created
```